




## Adapter PVC metric Rp

### Model:

- With solvent cement spigot metric and parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC



d (mm)	Rp (inch)	PN (bar)	Part No.	SP weight (kg)	z (mm)	D (mm)	L (mm)	
20	½	10	<b>721 900 406</b>	10	0.012	22	28	37
25	¾	10	<b>721 900 407</b>	10	0.018	25	34	41
32	1	10	<b>721 900 408</b>	10	0.035	29	42	48
40	1 ¼	10	<b>721 900 409</b>	10	0.063	34	52	56
50	1 ½	10	<b>721 900 410</b>	10	0.097	40	62	61
63	2	10	<b>721 900 411</b>	5	0.170	49	77	74

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>