



Adapter socket nipple PVC metric R

Model:

- With solvent cement spigot/socket reducing metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC

d (mm)	d1 (mm)	R (inch)	PN (bar)	Part No.	SP	weight (kg)	z (mm)	z1 (mm)	s (mm)
12	16	3/8	16	721 910 555	10	0.010	35	23	27
16	20	1/2	16	721 910 556	10	0.016	42	28	32
20	25	3/4	16	721 910 557	10	0.023	47	31	36
25	32	1	16	721 910 558	10	0.040	54	35	46
32	40	1 1/4	16	721 910 559	10	0.061	60	38	55
40	50	1 1/2	16	721 910 560	10	0.094	66	40	65
50	63	2	16	721 910 561	5	0.164	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>